



Panel alternatives	B, E
Tilting height	615 mm
Volume net/gross	400 litres / 425 litres
Weight	510 kg
Transport package (WXDXH)	1880 x 1430 x 1650 / 580 kg

Connections:

Electric	#E2 2,2 kW, 400V, 3~, 10A, 50/60 Hz
Potable Cold water	#2 G1/2", 2...8 bar, Filtered to 50 microns, Soft Max 6°dH
Warm water (option)	#3 G1/2", 2...8 bar
Hot water (option)	#4 G1/2", 65°C, 2...8 bar
Soft water (option)	#5 G1/2", 2...8 bar, Filtered to 50 microns, Soft Max 6°dH
House steam	#6 G 3/4" 1,5...2 bar, 100 kg/h
Condensate	#7 G1/2"

Options (factory installation required):

Chill CH1 - Chill CH2 - Chill CH3 - Wash hose with spray pistol - Single hand faucet C/W
 Draw off valve - Energy optimization

Options:

- Strainer plate - Wash tool - Wing for dough - Whipping tool - Tool trolley - Wall bracket for mixing tools
- Cleaning Set

Head Office

131 Alexander Street
 Crows Nest NSW 2065
 Ph: +61 2 9966 9500
 Fax: +61 2 9966 9511

Brisbane

Ph: 1300 138 026
 Fax: +61 7 3878 9042
 M: +61 411 500 245

Melbourne

Ph: 1300 138 026
 Fax: 1300 138 027